250W LED 3 in 1 Beam, Spot, Wash Moving Head With Light Ring

300BSW

Light Source

Light Source: 250W LED Engine & 36pcsx0.5W RGB SMD LEDs Color Temperature Output: 7,000K Rated Source Life: up to 20,000 hours

Optical System

Advanced optical design to ensure precise gobos and colors

High - efficiency zoom optical system

Beam Angle: 7°-35°

Diameter of Front Lens: 165mm

Control and Program

4-Button touch panel

Display: LCD display

Protocols: DMX512, Automatic, Sound active, RDM, Art-Net

DMX Protocol modes: 2

Control channels: 17,21

Firmware Upgrade: Upgrade via DMX link or USB disk

Movement

Pan movement: 540°

Tilt movement: 260°

Automatic Pan/Tilt position correction

Moving-head operated with either 16-bit resolution

Fixation: Pan/ Tilt lock

Color

Linear CTO Color Correction: 2,700K-7,000K

1 x Color Wheel: 8 colors with 1 CTB Filter, plus open

Gobo

1 x Static Gobo Wheel: 1 static gobo wheel with 9 gobos plus open 1 x Rotating & Interchangable Gobo Wheel: 1 rotating gobo wheel

with 6 gobos with water gobos plus open

Gobo Diameter: 23.8mm Image Diameter: 14mm

Adjustable-speed rotating gobo in both directions

1 x Combinable Rotating and Indexable Prisms: one 4-facet prism

Other Effects

Outstanding strobe effect with variable speed

Motorized Zoom and Focus

4 Dimming Curves: Variable light adjustment from 0 to 100%

Electrical and Connectors

Input voltage range: 100-240V~ 50/60Hz

Power consumption: 350 W

Power In/Out: Power Connector in/out


Data In/Out: 3-pin or 5-pin XLR

Master Box size:430x332x660mm

Gross Weight: 16.2 kg (include carton, one-pack per carton)



Photometrics Diagram













Renderings










Size mm(in)





Functional Effect



Static Gobo Wheel







































Multi-angle product diagram







